



OPERATOR PRESENCE SYSTEM. Control handles for the boom swing, boom raise/lower and machine propel are equipped with an operator presence handle design which provides capacitance-sensing capability. This user-friendly operator presence system is intended to help protect the operator and enhance operator safety.



CONVENIENT BELT SERVICING. Belts on the SC292 are serviceable from one side of the machine with cutter drive belts being adjustable with movable idlers. Additionally, each belt set may be adjusted independently without affecting adjustment of other belts.



AUTOSWEEP® CONTROL SYSTEM. When equipped, the AutoSweep system monitors engine speed and automatically adjusts cutter wheel sweep rate, and is designed to reduce engine, drivetrain and structural stress.



TWO-SPEED GROUND DRIVE. The operator may choose a high-range or low-range ground speed setting of 0 - 133 fpm (0 - 40.5 m/min) to quickly move the machine or choose a slower speed when near the stump by utilizing a low-range setting of 0 - 66 fpm (0 - 20.1 m/min).



START EASIER. Equipped with a 26.5 hp (20 kW) EFI Kohler engine, the SC292 performs well in cold-weather starts, has reduced occurrence of engine flooding and provides improved fuel economy over comparable carbureted gas engines.



YELLOW JACKET[™] CUTTER SYSTEM. The Vermeer-exclusive Yellow Jacket cutter system is designed to provide faster, easier serviceability, as well as extended pocket and tooth life.



SC292 STUMP CUTTER

GENERAL

Length: 110" (279.4 cm) Width (with duals): 49.8" (126.5 cm) Width (without duals): 35" (88.9 cm) Height: 52" (132.1 cm) Weight: 1220 lb (553.4 kg) Weight: 1220 lb (553.4 kg) Weight (alternate): 1280 lb (580.6 kg) Type: Rubber tire self-propelled Ground speed: 66 fpm (20.1 m/min) to 133 fpm (40.5 m/min)

ENGINE

Make/Model: Kohler Command PRO EFI Gross horsepower: 26.5 hp (20 kW) Max torque: 44.3 ft-lb (60.1 Nm) Number of cylinders: 2 Fuel type: Gasoline Cooling medium: Air

CUTTING DIMENSIONS

Cutter wheel straight line dimension: 47" (119.4 cm) Cutter wheel cut above ground: 24" (61 cm) Cutter wheel cut below ground: 15" (38.1 cm)

CUTTER WHEEL

Cutter wheel diameter (without teeth): 17" (43.2 cm) Cutter wheel thickness: .5" (12.7 mm) Tooth style: Yellow Jacket cutter system Number of teeth: 16 Chip containment: 7.7 cu ft (.2 cu m) Flow control system: AutoSweep® Cutter wheel guard: Standard

CAPACITIES/ELECTRICAL

Fuel tank: 6 gal (22.7 L) Hydraulic tank: 4 gal (15.1 L) Pump flow at max rpm: 3.7 gpm (14 L/min) Electrical system: 12 V

OPTIONAL

AutoSweep® control system Two hydraulically controlled steering wheels with pivoting axle Extended warranty Special paint Planned maintenance Vermeer Confidence Plus® asset protection program

NOTES:

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Vermeer Confidence Plus, AutoSweep and Yellow Jacket are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Kohler is a registered trademark of Kohler Co

